

Sound & Light Alarm Hygro-thermometer A2000-EX

Features:

Sound & light alarm if user defined high/low values are exceeded.
Deviation manual calibration
External sensor could expand length to 50 meters.
Could add external sound & light alarm.
Could add delay alarm function, if the data exceed limit and return to normal within the delay time, the device will not alarm.
Display temperature, humidity, time as well as environment status simultaneously
MAX/MIN function key to show the maximum/minimum value
Desk-top placing or Wall Hanging.

Specifications

Temperature Accuracy $\pm 0.5^{\circ}\text{C}$
Humidity Accuracy $\pm 5\% \text{RH}$
Temperature Measurement Range $-40 \sim +85^{\circ}\text{C}$
Humidity Measurement Range $0 \sim 100\% \text{RH}$
Resolution $0.1^{\circ}\text{C} / 0.1\% \text{RH}$
Sensor type External sensor with 3 meters cable
Battery 9V Block Battery *1
Alarm Buzzer and light
Dimensions $135\text{mm} * 124\text{mm} * 35\text{mm} (5.31" * 4.88" * 1.37" \text{inch})$
LCD display area $97\text{mm} * 78\text{mm} (3.81" * 1.37")$
Weight 330g
Certificate CE, ISO
Accessories 9V Block Battery, user manual, screw