

Features and Functions

1. We add a function of indicator lights. These indicator lights show 20 different distances between the user with a receiver and the transmitter.
2. Most common frequencies are Rock Gold, Sand Gold, Silver, Bronze, Brass, and Precious Stone.
3. Detecting Range: 100-1500m
4. Detecting Depth: 5-70m
5. After tracking target, you will have some idea of the identification and the exact pinpoint.
6. The face (front) of the transmitter has six LEDs (channel indicator lights) across the top; each is labeled for a particular element.

Components

1. A grey case with aluminum trim, a handle and two locks
2. External Battery Port
3. The Belt Receiver
4. Head Phones
5. Receiving Rods
6. Battery Charger, AC/DC adapter, input AC 115V, output DC 9V
7. Antenna
8. Marker Flags
9. Operators Manual

Specifications

1. Max Detection: 1500m
2. Detect Range: 100-1500m
3. Rechargeable Battery: Continuous working 48 hours
4. Power: 850mA
5. Frequency: 433Mhz+/-150Khz
6. Inner Storage: EEPROM 16k*8Bit
7. Voltage: 9~12VDC
8. Temperature Range: -40~85
9. Operating Humidity: 0~95% (non-condensing)
10. Ultrasonic Frequency: 400-3000Mhz+/-150Khz
11. Weight: 14LBS

Package

1. Size/Unit: 520*185*350mm
2. Weight/Unit: 8kg
3. Qty./CTN: 1unit
4. Size/CTN: 503*305*164mm
5. G.W./CTN: 8kg